

MODEL 155

Single Offset Disc Harrow

KELLO-BILT



Features

- Heavy frame and quality components.
- Make maximum use of your small horsepower tractor.
- Small plots, row crops, berries, orchards, and weed control.
- Kello-Bilt Oil Bath Bearing System - tapered roller bearings sealed with Duo-Cone® seals.
- Simple, efficient design for long life and easy operation.

Specifications

Model Number	Working Width ft.	Weight (lbs)	Weight per Disc (lbs)*	Tractor Draw Bar Horsepower**
155-1924B	6'9"	3,152	197	40+
155-2124B	7'6"	3,408	189	45+
155-2324B	8'2"	3,620	181	50+
155-2524B	9'	3,831	174	55+
155-2724B	9'8"	3,953	165	60+
155-2924B	10'6"	4,074	157	65+
155-3324B	12'	4,351	145	70+

* Does not include tapered furrow filler discs.

** Drawbar horsepower requirements vary with soil conditions, topography, weight added to harrow, and tractor type (steel track, rubber track, or rubber tire).

Kello-Bilt Inc. reserves the right to change pricing and specifications without notice.

MODEL 155

Single Offset Disc Harrow



Frame

5" x 3" x 3/8" high strength steel tube, fully welded and reinforced.



Disc Blades

1/4" x 24" notched disc blades front and rear. Optional smooth blades are available.



Bearings

Oil bath, back-to-back tapered roller bearings in heavy ductile cast housing c/w floating Duo-Cone® seals. Bearings operate in 90W gear oil for constant lubrication. Bearing comes complete with wear plate.



Hubs/Tires

9.5L x 15 6 ply implement tires (2) mounted on 6 bolt hub assemblies.



Gang Shaft

1 5/8" heat treated high strength alloy steel, threaded at both ends.



Hydraulics

4" x 8" hydraulic cylinder complete with hoses, depth control segments and cylinder transport lock.



Spacing

9" spacing, achieved with precision machined cast steel spools.



Standard

5000lb hitch jack, safety chain, slow moving vehicle sign, plated grade 8 fasteners, gang wrench (2), transport safety locks, and separate fore/aft and transport level controls.



16 Belich Crescent | Red Deer County, AB, Canada T4S 2K5

Phone: (403) 347-9500 | Fax: (403) 347-3724

Toll Free: 1-877-613-9500

Email: info@kello-bilt.com | www.kello-bilt.com

 [facebook@kello-bilt.com](https://www.facebook.com/kello-bilt.com)

 [instagram@kello-bilt.com](https://www.instagram.com/kello-bilt.com)

 [twitter@kello-bilt.com](https://twitter.com/kello-bilt.com)