


MODEL 800

Single Offset Breaking Disc



Features

The Kello-Bilt Model 800 offset disc is specifically designed to meet the extreme conditions encountered in the construction industry. For over 25 years these rugged discs have been employed to clear land, build roads

and dams, reclaim mine sites, mix and dry soils, and prepare land for reforestation throughout North America.

KELLO-BILT OIL BATH BEARING SYSTEM

Back-to-back tapered bearings in large cast steel housings with metal oil seals. Tapered bearings are designed for thrust unlike ball bearings used by other manufactures. Oil bath bearings provide a low maintenance, high quality solution that is essential in any industrial application.

Specifications

Model Number	Working Width ft.	Weight (lbs)	Weight per Disc (lbs)*	Tractor Draw Bar Horsepower**
800-2432B	13'	16,550	689	260+
800-2832B	15'	17,680	631	280+
800-3232B	17'6"	18,900	590	300+
800-3632B	20'	20,210	561	350+

* Does not include tapered furrow filler discs.

**Draw Bar Horsepower requirements vary with soil conditions, topography, weight added to harrow, and tractor type (steel track, rubber track, or rubber tire).

Kello-Bilt Inc. reserves the right to change pricing and specifications without notice.

MODEL 800

Single Offset Breaking Disc



Frame

8" x 8" x 1/2" high strength steel tube frame, 7" x 7" x 1/2" high strength steel tube gang bars, fully welded and reinforced.



Disc Blades

1/2" x 32" notched disc blades front and rear. 36" and 42" disc blades are an option.



Bearings

Oil bath, back-to-back tapered roller bearings in heavy ductile cast housing c/w floating Duo-Cone® seals. Bearings operate in 90W gear oil for constant lubrication. Bearing comes complete with wear plate.



Hubs/Tires

385/65R22.5 Super Single Radial heavy industrial tires mounted on 10 bolt stud hub. 600/50R22.5 Flotation Tires are optional.



Gang Shaft

2 1/2" heat treated high strength alloy steel, threaded at both ends.



Hydraulics

5" x 20" hydraulic cylinder complete with hoses and cylinder transport lock.



Spacing

14" fabricated heavy steel spacer spools designed to maintain gang tightness. 17" and 20" spacing is optional.



Standard

7000lb hitch jack, safety chain, slow moving vehicle sign, plated grade 8 fasteners, transport safety locks, gang wrench (2), separate fore/aft and transport level controls, and a heavy swivel flapper hook-up.



16 Belich Crescent | Red Deer County, AB, Canada T4S 2K5

Phone: (403) 347-9500 | Fax: (403) 347-3724

Toll Free: 1-877-613-9500

Email: info@kello-bilt.com | www.kello-bilt.com

 [facebook@kello-bilt.com](https://www.facebook.com/kello-bilt.com)

 [instagram@kello-bilt.com](https://www.instagram.com/kello-bilt.com)

 [twitter@kello-bilt.com](https://twitter.com/kello-bilt.com)