


MODEL
225TSW
Tandem Double Wing Disc



Features

- Massive Weldments / Superior Components
- Plow down heavy straw, corn, grass, or vegetable residue, remove old hay or pasture fields.
- Kello-Bilt Oil Bath Bearing System - tapered roller bearings sealed with Duo-Cone® seals
- Folding wings with narrow width for ease of transport.
- Three section design for maximum flexibility and weight distribution.
- Rugged, no gimmick design for long life and easy operation.

Specifications

Model Number	Working Width ft.	Weight (lbs)	Weight per Disc (lbs)*	Tractor Draw Bar Horsepower**
225TSW-4626B	18'	17,270	454	200+
225TSW-5026B	19'6"	17,670	420	220+
225TSW-5426B	21'	18,080	393	240+
225TSW-5826B	23'	19,490	390	260+
225TSW-7426B	29'	24,640	373	310+
225TSW-8226B	32'	25,570	346	340+

* Does not include tapered furrow filler discs.

** Drawbar horsepower requirements vary with soil conditions, topography, weight added to harrow, and tractor type (steel track, rubber track, or rubber tire). Kello-Bilt Inc. reserves the right to change pricing and specifications without notice.

MODEL 225TSW

Tandem Double Wing Disc



Frame

6" x 4" x 3/8" high strength steel tube, fully welded and reinforced.



Disc Blades

5/16" x 26" notched disc blades front and rear.
5/16" x 28" notched disc blades are available as well as wavy or smooth blades.



Bearings

Oil bath, back-to-back tapered roller bearings in heavy ductile cast housing c/w floating Duo-Cone® seals. Bearings operate in 90W gear oil for constant lubrication. Bearing comes complete with wear plate.



Hubs/Tires

12.5L x 15 12 ply highway implement tires mounted on 8 bolt hub assemblies.



Gang Shaft

2 1/8" heat treated high strength alloy steel, threaded at both ends.



Hydraulics

5" diameter hydraulic cylinders complete with hoses, depth control segments and cylinder transport lock.



Spacing

10 1/2" fabricated steel spacer spools designed to maintain gang tightness.



Standard

7000lb hitch jack, safety chain, slow moving vehicle sign, plated grade 8 fasteners, transport safety locks, gang wrench (2), and separate fore/aft and transport level controls.



16 Belich Crescent | Red Deer County, AB, Canada T4S 2K5

Phone: (403) 347-9500 | Fax: (403) 347-3724

Toll Free: 1-877-613-9500

Email: info@kello-bilt.com | www.kello-bilt.com

 [facebook@kello-bilt.com](https://www.facebook.com/kello-bilt.com)

 [instagram@kello-bilt.com](https://www.instagram.com/kello-bilt.com)

 [twitter@kello-bilt.com](https://twitter.com/kello-bilt.com)